

Agricultural

Attachments and Implements

Primers and Top Coats



Pronto Industrial Paints

Award Winning British Coatings Manufacturer

Agricultural

Attachments and Implements

Primers and Top Coats

Primers suitable for application by spray

203:406 is a ready thinned, medium build, single component, 'universal' transport primer based on a high performance modified alkyd resin with excellent recoating properties. It is designed for application by conventional spray.

203:425 has been specially formulated to give extended wet edge times to enable the painting of larger trailer chassis by airless spray.

Both primers provide good anti-corrosive protection for commercial vehicles, trailers, plant and agricultural equipment etc., and can be overcoated with many types of topcoat. **203:406** is touch dry in 15 minutes, **203:425** is touch dry in 30 mins and both are through Dry in 1-2 hours. Coverage is 8m² per litre.

Top coat suitable for application by spray

300:300 QD Pu is a high performance single component topcoat, specially formulated to give the performance benefits of polyurethane alkyd resin technology. It is designed for the coating of vehicle trailers, chassis, agricultural implements and general machinery. It offers improved durability, drying, film hardness and an increased resistance to cleaning chemicals etc. Touch dry in 1½ - 2½ hours and Through Dry overnight. Coverage is 13.3m² per litre.



Primer suitable for application by brush/roller

310:006 Air Drying High Build Zinc Phosphate Primer is an air drying primer with excellent covering properties. It is designed to enable professional painting of steel substrates. Theoretical coverage is 10m² per litre.

Top coat suitable for application by brush/roller

Agrisheen AD Protective Finish **308:200** is a single component moderately fast drying topcoat which is specially formulated on a high quality alkyd resin system which is thinned with white spirit. It has been specially formulated for use on agricultural implements and general machinery and dries relatively quickly to give a durable hard gloss finish which, once fully cured, is resistant to a range of oils and petrol. Touch dry in 1½ - 2½ hours and full cure 7 days. Theoretical coverage is 10m² per litre.



Familiarise yourself with the relevant Data Sheets before using these products. To obtain your copy call on 01246 857777.

Head Office

Stainsby Close
Holmewood Industrial Estate
Chesterfield
S42 5UG

Tel : 01246 857777

Fax : 01246 857978

Email : info@prontopaints.co.uk

www.prontopaints.co.uk



Pronto Industrial Paints

Award Winning British Coatings Manufacturer